

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04M 3/42, H04Q 7/22	A2	(11) International Publication Number: WO 99/25107 (43) International Publication Date: 20 May 1999 (20.05.99)
(21) International Application Number: PCT/SE98/01988 (22) International Filing Date: 3 November 1998 (03.11.98) (30) Priority Data: 9704058-8 6 November 1997 (06.11.97) SE (71) Applicant (for all designated States except US): TELIA AB (publ) [SE/SE]; Mårbackagatan 11, S-123 86 Farsta (SE). (72) Inventors; and (75) Inventors/Applicants (for US only): FRANK, Robert [SE/SE]; Torggatan 16F, S-185 32 Vaxholm (SE). WINROTH, Mats, Olof [SE/SE]; Lyckogången 4, S-135 54 Tyresö (SE). (74) Agent: PRAGSTEN, Rolf; Telia Research AB, Vitsandsgatan 9, S-123 86 Farsta (SE).		(81) Designated States: EE, JP, LT, LV, NO, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>Without international search report and to be republished upon receipt of that report.</i>
(54) Title: CALL SETUP IN MOBILE SYSTEMS (57) Abstract The invention relates to a method at a mobile tele and data communication system, which makes possible for an A-subscriber to transmit data to an application in the B-subscriber's mobile terminal in connection with the call setup. Examples of transferred data can be information which in the B-subscriber's mobile terminal executes a specific ringing melody, a personal logotype etc. The invention is characterized in that UUS is used as carrier to, at the setup, transfer this data information to the application in the B-subscriber's mobile terminal.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

TITLE OF THE INVENTION: CALL SETUP IN MOBILE SYSTEMS

Field of the invention

The present invention relates to a method at a mobile
5 tele and data communication system for call setup between an
A-subscriber and a B-subscriber.

Prior art

In the GSM of today there is no possibility for a GSM-
10 user to, at calling, transfer a personal ringing signal to a
receiving GSM-mobile. In Nokia's "Smart Messaging"-concept a
user can collect a ringing signal to his/her own Nokia 8110
via the radio interface, but cannot transmit a ringing
signal at calling another GSM-customer. Neither can the
15 user, at the setup of a call, transfer an application which,
for instance, might be a personal graphic symbol, a simple
moving graphic picture, or a hypertext page, which can be
shown on the display of the receiving GSM-mobile. Moreover,
there is no possibility to authenticate a user already at
20 the setup of the call. One, or possibly all, of these
functions would certainly become very popular services in
GSM if they would be realized.

The problem consequently can be summarized in that an
A-subscriber cannot transmit data to an application in the
25 B-subscriber's mobile in connection with the setup of the
call. Examples of data may be a specific ringing melody, a
personal logotype etc.

The aim of the following invention consequently is to
solve this problem.

30 Summary of the invention

The above mentioned aim is achieved by a method at a
mobile tele and data communication system for setup of call
between an A-subscriber and a B-subscriber, where UUS is
35 used as carrier to, at said setup of call, transfer data
information to an application at said B-subscriber.

A big advantage of the invention is that it can be used to differentiate the service offering of different operators. Operators can offer new, attractive service functions, which of course will increase their revenues.

5 Further characteristics of the invention are given in the subclaims.

In the following a detailed description of an embodiment of the invention is given.

10 Detailed description of the invention

With today's technology data to an application in the B-subscriber's mobile cannot, as has been mentioned above, be transferred at setup of a call, for instance a personal ringing melody which is played instead of a default ringing
15 signal, that a personal logotype is shown on the receiver's display, or that an authentication can be made already at the setup of a call.

The invention attends to this by means of the functions which now will be described below.

20 SIM Application Toolkit is included in GSM phase 2+, and i.a. gives SIM possibility to show text in mobile display, transmit SMS, establish call, transmit USSD-string, initiate dialogue with mobile users and
25 mechanism to transfer data to SIM from the network. USSD stands for Unstructured Supplementary Services Data, and is a data channel which can be used to transmit data between network and mobile. In phase 2+ USSD is developed to become a general carrier.

30 Java Card API is a java standard which has been developed for smart cards (for instance GSM's SIM is a smart card). Java Card API makes it possible to implement a java interpreter on the SIM, which i.a.
35 results in that the operator has possibility to either download an own-developed java application on the card,

before it is handed over to the customer, or load down an application via, for instance, SMS. Together with SIM Application Toolkit, there will be possibilities to develop very advanced functions and applications.

5 Embedded Java, Personal Java, are java standards which have been developed to be used in products with limited processor capacity and memory. A typical product can be a mobile telephone. The mobile manufacturer has for a
10 long time worked with Java in the mobile terminal, but now also work within ETSI has started to achieve a standard. Within a few years all "high end" telephones will support Java (according to well-informed sources at Ericsson Mobile). Java applications can be
15 transferred to the mobile in a number of different ways: from SIM (where for instance an operator specific application can be located), via SMS, USSD, GPRS, or data from the network, and via i.a. UUS from another user.

20 UUS (User to User Signalling): The function is inherited from ISD and supports transmission of smaller amounts of user data at the setup, during call, and at the termination of the call. In the case with UUS at
25 the setup, there is a field specified in the "SET UP"-message, where up to 35 octets of user information can be transferred to the B-subscriber. During a call, one or more continuous packets of 131 octets of user data can be transferred on the main signalling channel,
30 FACCH.

The invention also can be used in another or future system where there are, or will be, functions similar to those described above. One example is ISDN, where the
35 functionality already exists.

Provided that the GSM-mobile and SIM supports Java, SIM Application Toolkit and UUS, the problems above can be solved in the following way.

- 5 1. A GSM-user establishes a connection towards a GSM-mobile. By USS a frame, max. 35 octets long, consisting of an information header (of one or two octets) and a data field, is transferred. The information in the header can consist of
10 application as well as how many octets user data the frame contains. It means that the maximal amount of application data which can be transferred to an application in the B-subscriber's GSM-telephone consists of 33 or 34
15 octets.
2. When the receiving side detects that the SET-UP-message contains a UUS-data field, the UUS data is transferred to an application in the mobile (or the SIM) which reads the data header, where
20 information exists about which application at the SIM, or in the mobiles that shall be started.
3. The application, which establishes the call and transmits the UUS-message, can use SIM
25 Application Toolkit to manage call setup, provided that SIM Application Toolkit is extended with functionality for UUS. Similar functionality, however, will exist via the Java interpreter in the mobile.

30 The invention is characterized in:

- that UUS (User to User Signalling) is used as carrier to, at the setup, transfer data information to an application in called GSM-mobile;

- that the data frame, which at setup is maximally 35 octets, consists of a header containing information about application, length of user data, etc, and of a user data field, 33 or 34 octets;
- 5 - that one application at the A-subscriber establishes a call setup where a UUS-data packet is incorporated;
- that one application at the B-subscriber, on basis of the header information in the UUS-packet, can decide requested application and start this application in the B-subscriber's mobile;
- 10 - that the applications are developed in Java, or other suitable language;
- 15 - that one application is that a user can define his/her own personal melody, which at setup of call is transmitted to the B-subscriber's mobile, where it is played back, instead of default ringing signal;
- 20 - that one application is that a graphic symbol, moving or static, is shown on the B-subscriber's mobile. For a moving picture, a library of movement patterns is required in receiving application;
- 25 - that one application is authentication of the A-subscriber already at setup;
- 30 - that UUS is defined also for ISDN, so the invention can be used also in environment with only ISDN or ISDN-GSM;
- that the invention, as a whole or parts of it, applies to present and future mobile telephone systems with similar functionality;
- 35

- that the applications can be downloaded on SIM-cards, by the operator, already at subscription.
- In the following a number of examples of possible applications of the invention are given:
- An A-subscriber's personal ringing signal is transferred and played back as ringing signal in the B-subscriber's GSM mobile telephone:

- In the A-subscriber's mobile, an application is required which can set up a call which includes a UUS-data packet.

- In the B-subscriber's mobile, one or two applications are required (can, but must not necessarily be a Java application) which from the header information of the data frame can decide which application that is intended and start that application, here a ringing signal application, with the user data in the frame as in-argument. Because the maximal amount of data that UUS can transmit at call setup is 35 octets, more than 35 tones can be transferred, where each tone, tone pitch and duration can be described by 6 or 7 bits.

The application instead can consist of a simple bitmapped symbol which moves across the screen. The symbol can, for instance, consist of 32 octets (for instance a 16x16 bits picture), at which other data can be used to select a movement pattern from a library which is in the B-subscriber's application.

Together with a mobile-adapted WWW-browser, a short hypertext page can be transferred to the mobile, where the B-subscriber with a pointer marks a line, and by means of USSD in SMS transmits a request about to get,

via SMS or USSD (or possibly UUS), wanted information. On the receiving side, an application that can reformat the only 33 or 34 octet long information to suitable format, is required.

5 A security application can be used to authenticate a calling mobile already at the call setup. It can be used, for instance, at access to its bank, access to a premises network, or even for authenticating a person
10 who is calling another GSM-mobile.

The application in the mobile, alternatively the SIM-card, may require that a password is stated before the call is set up. In the future - depending on when the
15 technology is ready for implementation in GSM - the application in the mobile can, instead of a password, use voice authentication to identify the A-subscriber before the call is set up. After correct password being entered, the application works out a code word, based
20 on, for instance, IMSI, the password (alt. approved voice authentication) and code key (stored in the application). The code word is transferred, via UUS to a receiver application on the other side, which has access to code key and list of user identities. The
25 receiver by that can authenticate the calling subscriber via the transferred code word.

The application which, for instance, a bank customer uses in such a process can be transferred from the bank
30 to him/her via, for instance, USSD or SMS. A code word for the application is communicated to the bank customer in another way. In the same way a mobile subscriber can transmit a security application to another mobile subscriber.

Specific applications can be operator specific by downloading these on the SIM-cards when the customer subscribe. This make possibilites for differentiation.

5 Since the processor capacity of the SIM of today is limited, the application possibly has to be transferred from the memory in SIM to a memory in the mobile, from where the application later can be run via, for instance, a Java interpreter in the mobile. Data from
10 the UUS-message can be enclosed as argument to the application.

Another method, which can be used to transfer an application to a mobile, can be from an Internet server
15 via mobile-adapted WWW-browser. One example is "Smart Messaging", which is Nokia's name for a WWW-similar application which can be run in a mobile, where data can be transferred via SMS or USSD.

20 Further, an application can be downloaded to the telephone via the serial interface of the mobile.

The application must be possible to switch off, in order to retrieve the normal ringing signal behaviour
25 when the user so wishes.

The above mentioned is only to be regarded as an advantageous embodiment of the invention, and the extent of the invention is only defined by what is indicated in the
30 following patent claims.

PATENT CLAIMS

1. Method at a mobile tele and data communication system for call setup between an A-subscriber and a B-subscriber, c h a r a c t e r i z e d in that UUS is used as carrier to, at said call setup, transfer data information to at least one application at said B-subscriber.

2. Method according to patent claim 1, c h a r a c t e r i z e d in that said data information consists of a data frame including a header and a data field, at which said header contains information about which application at said B-subscriber that is intended, and that said data field constitutes in-argument to said application for execution of said at least one application at said B-subscriber.

3. Method according to any of the patent claims 1 or 2, c h a r a c t e r i z e d in that said at least one application is implemented in a SIM-card at the B-subscriber's mobile terminal.

4. Method according to the patent claims 1 or 2, c h a r a c t e r i z e d in that the A-subscriber's mobile terminal utilizes SIM Application Toolkit to transfer said data information to said B-subscriber's mobile terminal.

5. Method according to the patent claims 3, or 4, c h a r a c t e r i z e d in that said at least one application is developed in Java.

6. Method according to patent claim 5, c h a r a c t e r i z e d in that JAVA-applications are transferred to said A-subscriber's, respective B-subscriber's, mobile terminals via SMS, USSD or GPRS.

7. Method according to any of the previous patent claims, c h a r a c t e r i z e d in that said mobile terminals are GSM-terminals with SIM-cards which support JAVA, SIM Application Toolkit and UUS.

8. Method according to patent claim 7,

c h a r a c t e r i z e d in that it includes the steps that:

5 - said A-subscriber's GSM-terminal establishes a call towards said B-subscriber's GSM-terminal, at which a SIM Application Toolkit function is extended with functionality for UUS and attends to transfer of said data information, i.e the UUS-message, to said B-subscriber's mobile terminal;

10 - said B-subscriber's mobile terminal detects said data information, and said header in said data information defines which application that shall be executed, and that said data field in said data information
15 constitutes in-parameter to said application which shall be executed in the B-subscriber's mobile terminal.

20 9. Method according to any of the previous patent claims, c h a r a c t e r i z e d in that said application is that said A-subscriber can define his/her own personal melody which at call setup is transferred to said B-subscriber's mobile terminal, where said melody is played.

25 10. Method according to any of the claims 1-8, c h a r a c t e r i z e d in that said application relates to an authentication of said A-subscriber directly at the call setup towards said B-subscriber.

30 11. Method according to patent claim 10, c h a r a c t e r i z e d in that said application relates to that a password is given before the call is set up towards said B-subscriber.

35 12. Method according to patent claim 10,

c h a r a c t e r i z e d in that said application relates to voice authentication to identify said A-subscriber, before the call is set up towards said B-subscriber.

THIS PAGE BLANK (USPTO)